GFRG-S

GLASS FIBER REINFORCED GYPSUM SQUARE CORNER



Application


Glass fiber reinforced gypsum, ceiling access doors are designed to blend seamlessly into drywall ceilings.

Product Features

- Tapered edge for joint tape
- Easily textured
- Lightweight
- No cracking or shrinkage
- Mold and moisture resistant

GFRG-S Access Door Specifications:

- Shell Thickness = 1/8" to 3/16"
- Fastener Test Pull Out (wood stud) = 525 lb. avg.
- Fastener Test Pull Out (metal stud) = 215 lb. avg.
- Fastener Push Through Test = 350 lb. avg.
- Fuel Contribution (ASTM-E84-80) = 0
- Flame Spread (ASTM-E84-80) = 0
- Smoke Index (ASTM-E84-80) = 0
- Combustion (ASTM-E84-80) = 0
- Shell Thickness = 1/8" to 3/16"
- CLASS A NON-RATED



GFRG-S STANDARD SIZES

(Special sizes available upon request)

Door Size	Ceiling Opening	Weight
Inches (mm)	Inches (mm)	LBS (kg)
9 x 9 (229 x 229)	15 x 15 (381 x 381)	5.6 (2.5)
12 x 12 (305 x 305)	18 x 18 (457 x 457)	8.2 (3.7)
16 x 16 (406 x 406)	22 x 22 (559 x 559)	11.3 (5.1)
18 x 18 (457 x 457)	24 x 24 (610 x 610)	14.7 (6.7)
24 x 24 (610 x 610)	30 x 30 (762 x 762)	16.9 (7.7)

For detailed specifications see submittal sheet

U.S.A.: info@acudor.com / 800-722-0501 **CANADA:** info@acudor.ca / 844-228-3671 **INTERNATIONAL:** info@acudorintl.com / 905-428-2240
MEXICO: infomx@acudor.com / +52-844-171-6595 **INDIA / MIDDLE EAST / NORTH AFRICA:** ap-imea@acudor.com / +971-4-399-6966 **SITE:** www.acudor.com

This document contains proprietary information which is the property of Acudor Products. It shall not be modified, copied, furnished, nor distributed (in whole or in part) without proper authorization. Copyright © 2020 Acudor Products.